

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

**Product Description:** Lithium tert-butoxide, solution in THF, stabilized  
**Cat No. :** 379310000; 379311000; 379318000

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended Use** Laboratory chemicals.  
**Uses advised against** No Information available

### 1.3. Details of the supplier of the safety data sheet

#### Company

**UK entity/business name**  
Fisher Scientific UK  
Bishop Meadow Road,  
Loughborough, Leicestershire LE11 5RG, United Kingdom

**EU entity/business name**  
Thermo Fisher Scientific  
Janssen Pharmaceuticaaan 3a, 2440 Geel, Belgium

**E-mail address** begel.sdsdesk@thermofisher.com

### 1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11  
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99  
**CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

#### GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

#### **Physical hazards**

Flammable liquids Category 2 (H225)

#### **Health hazards**

Skin Corrosion/Irritation	Category 1 B (H314)
Serious Eye Damage/Eye Irritation	Category 1 (H318)
Carcinogenicity	Category 2 (H351)
Specific target organ toxicity - (single exposure)	Category 3 (H335) (H336)

# SAFETY DATA SHEET

Lithium tert-butoxide, solution in THF, stabilized

Revision Date 06-Dec-2024

## Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

## 2.2. Label elements



Signal Word

Danger

## Hazard Statements

H225 - Highly flammable liquid and vapor  
H314 - Causes severe skin burns and eye damage  
H335 - May cause respiratory irritation  
H336 - May cause drowsiness or dizziness  
H351 - Suspected of causing cancer  
EUH014 - Reacts violently with water  
EUH019 - May form explosive peroxides

## Precautionary Statements

P280 - Wear protective gloves/protective clothing/eye protection/face protection  
P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P310 - Immediately call a POISON CENTER or doctor/physician  
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

## 2.3. Other hazards

Reacts violently with water

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

Component	CAS No	EC No	Weight %	GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Tetrahydrofuran	109-99-9	203-726-8	79-81	Flam. Liq. 2 (H225) Acute Tox. 4 (H302) Eye Irrit. 2 (H319) STOT SE 3 (H335) STOT SE 3 (H336)

# SAFETY DATA SHEET

Lithium tert-butoxide, solution in THF, stabilized

Revision Date 06-Dec-2024

				Carc. 2 (H351) (EUH019)
2-Propanol, 2-methyl-, lithium salt	1907-33-1	EEC No. 217-611-5	19-21	Skin Corr. 1B (H314) Eye Dam. 1 (H318) Acute Tox. 4 (H302) Flam. Sol. 2 (H228) (EUH014)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Tetrahydrofuran	Acute Tox. 4 :: C>82.5% Eye Irrit. 2 :: C>=25% STOT SE 3 :: C>=25%	-	-

Components	Reach Registration Number
Tetrahydrofuran	01-2119444314-46
2-Propanol, 2-methyl-, lithium salt	01-2120138357-54

Full text of Hazard Statements: see section 16

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

<b>General Advice</b>	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
<b>Skin Contact</b>	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.
<b>Ingestion</b>	Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately.
<b>Inhalation</b>	If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately.
<b>Self-Protection of the First Aider</b>	Remove all sources of ignition.

### 4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Causes central nervous system depression

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes to Physician</b>	Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure. Treat symptomatically. Symptoms may be delayed.
---------------------------	--

# SAFETY DATA SHEET

Lithium tert-butoxide, solution in THF, stabilized

Revision Date 06-Dec-2024

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

#### **Suitable Extinguishing Media**

Dry chemical. Dry sand. Alcohol resistant foam. Water mist may be used to cool closed containers.

#### **Extinguishing media which must not be used for safety reasons**

Water. Carbon dioxide (CO<sub>2</sub>).

### 5.2. Special hazards arising from the substance or mixture

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors. Reacts violently with water. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

#### **Hazardous Combustion Products**

Thermal decomposition can lead to release of irritating gases and vapors.

### 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges. Refer to protective measures listed in Sections 7 and 8

### 6.2. Environmental precautions

Should not be released into the environment.

### 6.3. Methods and material for containment and cleaning up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material. Do not expose spill to water. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

### 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water. If peroxide formation is suspected, do not open or move container. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

# SAFETY DATA SHEET

Lithium tert-butoxide, solution in THF, stabilized

Revision Date 06-Dec-2024

## Hygiene Measures

When using do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

## 7.2. Conditions for safe storage, including any incompatibilities

Keep in properly labeled containers. Keep away from water or moist air. Keep away from heat, sparks and flame. Shelf life 12 months. May form explosive peroxides on prolonged storage. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area.

**Technical Rules for Hazardous Substances (TRGS) 510** Class 3  
**Storage Class (LGK) (Germany)**

## 7.3. Specific end use(s)

Use in laboratories

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Tetrahydrofuran	STEL: 100 ppm 15 min STEL: 300 mg/m <sup>3</sup> 15 min TWA: 50 ppm 8 hr TWA: 150 mg/m <sup>3</sup> 8 hr Skin	TWA: 50 ppm (8h) TWA: 150 mg/m <sup>3</sup> (8h) STEL: 100 ppm (15min) STEL: 300 mg/m <sup>3</sup> (15min) Skin	TWA: 50 ppm 8 hr. TWA: 150 mg/m <sup>3</sup> 8 hr. STEL: 100 ppm 15 min STEL: 300 mg/m <sup>3</sup> 15 min Skin

#### Biological limit values

List source(s):

#### Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Tetrahydrofuran 109-99-9 ( 79-81 )				DNEL = 12.6mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Tetrahydrofuran 109-99-9 ( 79-81 )	DNEL = 300mg/m <sup>3</sup>	DNEL = 96mg/m <sup>3</sup>	DNEL = 150mg/m <sup>3</sup>	DNEL = 72.4mg/m <sup>3</sup>

#### Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water	Water Intermittent	Microorganisms in	Soil (Agriculture)
-----------	-------------	-------------	--------------------	-------------------	--------------------

# SAFETY DATA SHEET

Lithium tert-butoxide, solution in THF, stabilized

Revision Date 06-Dec-2024

		<b>sediment</b>		<b>sewage treatment</b>	
Tetrahydrofuran 109-99-9 ( 79-81 )	PNEC = 4.32mg/L	PNEC = 23.3mg/kg sediment dw	PNEC = 21.6mg/L	PNEC = 4.6mg/L	PNEC = 2.13mg/kg soil dw

<b>Component</b>	<b>Marine water</b>	<b>Marine water sediment</b>	<b>Marine water intermittent</b>	<b>Food chain</b>	<b>Air</b>
Tetrahydrofuran 109-99-9 ( 79-81 )	PNEC = 0.432mg/L	PNEC = 2.33mg/kg sediment dw		PNEC = 67mg/kg food	

## 8.2. Exposure controls

### Engineering Measures

Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

### Personal protective equipment

**Eye Protection** Goggles (European standard - EN 166)

**Hand Protection** Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Butyl rubber	See manufacturers recommendations	-	EN 374	(minimum requirement)
Neoprene gloves				

**Skin and body protection** Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

**Respiratory Protection** When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.  
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

**Large scale/emergency use** Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced  
**Recommended Filter type:** low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387

**Small scale/Laboratory use** Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.  
**Recommended half mask:-** Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141  
When RPE is used a face piece Fit Test should be conducted

**Environmental exposure controls** No information available.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

# SAFETY DATA SHEET

Lithium tert-butoxide, solution in THF, stabilized

Revision Date 06-Dec-2024

<b>Physical State</b>	Liquid	
<b>Appearance</b>	Light yellow	
<b>Odor</b>	Irritating	
<b>Odor Threshold</b>	No data available	
<b>Melting Point/Range</b>	No data available	
<b>Softening Point</b>	No data available	
<b>Boiling Point/Range</b>	No information available	
<b>Flammability (liquid)</b>	Highly flammable	Estimated
<b>Flammability (solid,gas)</b>	Not applicable	Liquid
<b>Explosion Limits</b>	No data available	
<b>Flash Point</b>	No information available	<b>Method -</b> No information available
<b>Autoignition Temperature</b>	No data available	
<b>Decomposition Temperature</b>	No data available	
<b>pH</b>	No information available	
<b>Viscosity</b>	No data available	
<b>Water Solubility</b>	Reacts violently with water	
<b>Solubility in other solvents</b>	No information available	
<b>Partition Coefficient (n-octanol/water)</b>		
<b>Component</b>	<b>log Pow</b>	
Tetrahydrofuran	0.45	
<b>Vapor Pressure</b>	No data available	
<b>Density / Specific Gravity</b>	0.890	
<b>Bulk Density</b>	Not applicable	Liquid
<b>Vapor Density</b>	No data available	(Air = 1.0)
<b>Particle characteristics</b>	Not applicable (liquid)	

## 9.2. Other information

**Explosive Properties** Vapors may form explosive mixtures with air

## SECTION 10: STABILITY AND REACTIVITY

**10.1. Reactivity** ; Yes Water reactive

**10.2. Chemical stability** Reacts violently with water. Moisture sensitive.

### 10.3. Possibility of hazardous reactions

**Hazardous Polymerization** No information available.  
**Hazardous Reactions** None under normal processing. Reacts violently with water.

### 10.4. Conditions to avoid

Heating in air. Keep away from open flames, hot surfaces and sources of ignition. Exposure to moist air or water. Exposure to moisture.

### 10.5. Incompatible materials

Acids. Water. Oxidizing agent.

### 10.6. Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and vapors.

## SECTION 11: TOXICOLOGICAL INFORMATION

# SAFETY DATA SHEET

Lithium tert-butoxide, solution in THF, stabilized

Revision Date 06-Dec-2024

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### Product Information

**(a) acute toxicity;**

**Oral** Based on available data, the classification criteria are not met  
**Dermal** Based on available data, the classification criteria are not met  
**Inhalation** Based on available data, the classification criteria are not met

### Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Tetrahydrofuran	1650 mg/kg ( Rat )	> 2000 mg/kg (Rabbit)	180 mg/L ( Rat ) 1 h 53.9 mg/L ( Rat ) 4 h

**(b) skin corrosion/irritation;** Category 1 B

**(c) serious eye damage/irritation;** Category 1

**(d) respiratory or skin sensitization;**

**Respiratory** No data available  
**Skin** No data available

Component	Test method	Test species	Study result
Tetrahydrofuran 109-99-9 ( 79-81 )	Local Lymph Node Assay OECD Test Guideline 429	mouse	non-sensitising

**(e) germ cell mutagenicity;** No data available

Component	Test method	Test species	Study result
Tetrahydrofuran 109-99-9 ( 79-81 )	OECD Test Guideline 476 Gene cell mutation	in vivo Mammalian	negative
	OECD Test Guideline 473 Chromosomal aberration assay	in vitro Mammalian	negative

**(f) carcinogenicity;** Category 2

The table below indicates whether each agency has listed any ingredient as a carcinogen  
 Limited evidence of a carcinogenic effect

Component	EU	UK	Germany	IARC
Tetrahydrofuran				Group 2B

**(g) reproductive toxicity;** No data available

Component	Test method	Test species / Duration	Study result
Tetrahydrofuran 109-99-9 ( 79-81 )	OECD Test Guideline 416	Rat 2 Generation	NOAEL = 3,000 ppm

**(h) STOT-single exposure;** Category 3

**Results / Target organs** Respiratory system, Central nervous system (CNS).

**(i) STOT-repeated exposure;** No data available

**Target Organs** No information available.



# SAFETY DATA SHEET

Lithium tert-butoxide, solution in THF, stabilized

Revision Date 06-Dec-2024

(j) aspiration hazard; No data available

**Other Adverse Effects** The toxicological properties have not been fully investigated.

**Symptoms / effects, both acute and delayed** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Causes central nervous system depression.

## 11.2. Information on other hazards

**Endocrine Disrupting Properties** Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

**Ecotoxicity effects** Do not empty into drains. Reacts with water so no ecotoxicity data for the substance is available.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Tetrahydrofuran	2160 mg/l LC50 = 96 h Pimephales promelas Leuciscus idus: LC50: 2820 mg/L/48h	EC50 48 h 3485 mg/l EC50: >10000 mg/L/24h	

### 12.2. Persistence and degradability

**Persistence** Persistence is unlikely, based on information available.  
**Degradability** Reacts with water.  
**Degradation in sewage treatment plant** Reacts violently with water.

**12.3. Bioaccumulative potential** Bioaccumulation is unlikely; Product does not bioaccumulate due to reaction with water

Component	log Pow	Bioconcentration factor (BCF)
Tetrahydrofuran	0.45	No data available

### 12.4. Mobility in soil

The product is water soluble, and may spread in water systems. Reacts violently with water. Is predicted to have low mobility in the environment. Is not likely mobile in the environment. Highly mobile in soils.

**12.5. Results of PBT and vPvB assessment** Reacts violently with water.

### 12.6. Endocrine disrupting properties

#### Endocrine Disruptor Information

Component	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances
Tetrahydrofuran	Group III Chemical	

### 12.7. Other adverse effects

# SAFETY DATA SHEET

Lithium tert-butoxide, solution in THF, stabilized

Revision Date 06-Dec-2024

**Persistent Organic Pollutant** This product does not contain any known or suspected substance  
**Ozone Depletion Potential** This product does not contain any known or suspected substance

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Waste from Residues/Unused Products** Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

**Contaminated Packaging** Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

**European Waste Catalogue (EWC)** According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

**Other Information** Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms.

## SECTION 14: TRANSPORT INFORMATION

### IMDG/IMO

**14.1. UN number** UN2924  
**14.2. UN proper shipping name** Flammable liquid, corrosive, n.o.s.  
**Technical Shipping Name** Tetrahydrofuran, 2-Propanol, 2-methyl-, lithium salt  
**14.3. Transport hazard class(es)** 3  
**Subsidiary Hazard Class** 8  
**14.4. Packing group** II

### ADR

**14.1. UN number** UN2924  
**14.2. UN proper shipping name** Flammable liquid, corrosive, n.o.s.  
**Technical Shipping Name** Tetrahydrofuran, 2-Propanol, 2-methyl-, lithium salt  
**14.3. Transport hazard class(es)** 3  
**Subsidiary Hazard Class** 8  
**14.4. Packing group** II

### IATA

**14.1. UN number** UN2924  
**14.2. UN proper shipping name** Flammable liquid, corrosive, n.o.s.  
**Technical Shipping Name** Tetrahydrofuran, 2-Propanol, 2-methyl-, lithium salt  
**14.3. Transport hazard class(es)** 3  
**Subsidiary Hazard Class** 8  
**14.4. Packing group** II

**14.5. Environmental hazards** No hazards identified

**14.6. Special precautions for user** No special precautions required.

# SAFETY DATA SHEET

Lithium tert-butoxide, solution in THF, stabilized

Revision Date 06-Dec-2024

**14.7. Maritime transport in bulk according to IMO instruments** Not applicable, packaged goods

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Tetrahydrofuran	109-99-9	203-726-8	-	-	X	X	KE-33454	X	X
2-Propanol, 2-methyl-, lithium salt	1907-33-1	217-611-5	-	-	-	X	KE-22579	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Tetrahydrofuran	109-99-9	X	ACTIVE	X	-	X	X	X
2-Propanol, 2-methyl-, lithium salt	1907-33-1	X	ACTIVE	-	X	-	-	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

#### Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Tetrahydrofuran	109-99-9	-	Use restricted. See entry 75. (see link for restriction details)	-
2-Propanol, 2-methyl-, lithium salt	1907-33-1	-	-	-

#### REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

#### Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Tetrahydrofuran	109-99-9	Not applicable	Not applicable
2-Propanol, 2-methyl-, lithium salt	1907-33-1	Not applicable	Not applicable

#### Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

#### Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

# SAFETY DATA SHEET

Lithium tert-butoxide, solution in THF, stabilized

Revision Date 06-Dec-2024

## National Regulations

**UK** - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

**WGK Classification** Water endangering class = 1 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Tetrahydrofuran	WGK1	
2-Propanol, 2-methyl-, lithium salt	WGK1	

Component	France - INRS (Tables of occupational diseases)
Tetrahydrofuran	Tableaux des maladies professionnelles (TMP) - RG 84

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Tetrahydrofuran 109-99-9 (79-81)		Group I	

## 15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

## SECTION 16: OTHER INFORMATION

### Full text of H-Statements referred to under sections 2 and 3

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

H351 - Suspected of causing cancer

EUH014 - Reacts violently with water

EUH019 - May form explosive peroxides

H225 - Highly flammable liquid and vapor

H228 - Flammable solid

H302 - Harmful if swallowed

H319 - Causes serious eye irritation

### Legend

**CAS** - Chemical Abstracts Service

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**WEL** - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

**RPE** - Respiratory Protective Equipment

**TWA** - Time Weighted Average

**IARC** - International Agency for Research on Cancer Predicted No Effect Concentration (PNEC)

**LD50** - Lethal Dose 50%

# SAFETY DATA SHEET

Lithium tert-butoxide, solution in THF, stabilized

Revision Date 06-Dec-2024

**LC50** - Lethal Concentration 50%

**NOEC** - No Observed Effect Concentration

**PBT** - Persistent, Bioaccumulative, Toxic

**EC50** - Effective Concentration 50%

**POW** - Partition coefficient Octanol:Water

**vPvB** - very Persistent, very Bioaccumulative

**ADR** - European Agreement Concerning the International Carriage of Dangerous Goods by Road

**IMO/IMDG** - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

**ICAO/IATA** - International Civil Aviation Organization/International Air Transport Association

**MARPOL** - International Convention for the Prevention of Pollution from Ships

**ATE** - Acute Toxicity Estimate

**VOC** - (Volatile Organic Compound)

## Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

## Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

**Physical hazards** On basis of test data

**Health Hazards** Calculation method

**Environmental hazards** Calculation method

## Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Chemical incident response training.

**Revision Date** 06-Dec-2024

**Revision Summary** SDS sections updated: 5.

**This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.**

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**